

Flushing machine

TURN MACHINE OFF BEFORE STARTING THIS PROCESS





Lift bowl out of base and place in bucket



Drain the water in the tank by running both taps until empty.



Put your finger through the hole in the plastic plate and pull upwards to lift out.

Might need to twist it a bit to get it out.



Clean out any residue that might be in the tank with a clean cloth.

Option 3



Unscrew the plug at the back to drain the hot tank.



Have a bucket / jug ready under it to catch water



You will need about 4 liters of white vinegar undiluted.

This works best as it doesn't only disinfect but it also removes any calcium build up in the machine



Use a funnel to pour into the spout that leads to the hot tank until it overflows



Pour vinegar in the cold tank, until all pipes are covered or all calcium residue is submerged.

You can dilute with water, but more effective to use straight.

Cover the tank with cling wrap.

Let the vinegar sit in the machine for as long as possible, at least 4-5 days to work effectively.

It's a good idea to do this when going away on holiday





Drain vinegar by running both taps & unplugging hot pot plug at the back.



Rinse machine by flushing a few buckets of water run through it or place outside with a hose running water through it.



You can wedge a pair of pliers in the tap section to hold it down to let the water run out without having to hold down the taps.



Mix a bucket of water with 1 cup of bicarb soda



Pour the mixture into the machine and let it sit for 24 hours.





Drain again by running both taps & unplugging hot pot plug at the back.



Rinse machine by flushing a few buckets of water run through it or place outside with a hose running water through it.



Reassemble bowl & fill up again.